

MATERIAL SAFETY DATA SHEET

Red Rubber Sheet

Required under OSHA's hazard communication standard 29cfr 1910.1200

SECTION I – PRODUCT INFORMATION

Distributor's name: Allied Rubber & Gasket Company, Inc. – ARGCO
2610 Commerce Way
Vista, Ca 92081

In case of emergency: 703-773-2711

For information call: (800) 854-1015

Date prepared: 1/23/2007

Product name: Red "SBR" Rubber Sheet; Styrene Butadiene Rubber

SECTION II – INGREDIENTS AND HAZARDS

Fluoroelastomer 27%

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

| | | | |
|-----------------------------|-----------|--|------------------------------|
| Boiling point: | N/A | Vapor Pressure: | N/A |
| Vapor Density: | N/A | Specific Gravity (H₂O +1): | Not determined |
| Melting Point: | N/A | Evaporation Rate (Butyl Acetate =1) | N/A |
| Solubility in Water: | Insoluble | Appearance and Odor: | Red rubber sheet-rubber odor |

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Hazardous gases/vapors produced in fire are carbon monoxide. Wear a self-contained breathing apparatus and clothing. Hazardous decomposition products will be emitted in a fire and include carbon monoxide, carbon dioxide, and minor amount of toxic vapors possible. Fire fighters should use a self-contained breathing apparatus when fighting fires involving this material. Extinguishing agents may be water, foam, dry chemical or carbon dioxide.

SECTION V – REACTIVITY DATA

This is a stable material under normal use, handling, and storage conditions. Avoid high shear and high temperature situations. Hazardous decomposition products, and minor toxic vapors or gases. The importer can provide chemical resistance data upon written request. Hazardous polymerization will not occur.

SECTION VI – PRECAUTIONS FOR SAFE HANDLING & USE

If there is eye contact, flush eyes with clean running water for at least fifteen minutes. If irritation persists, consult a physician. Ignition of this material may result in the releases of toxic gases. Vapors may cause “polymer fume fever” which includes fever and chills. Symptoms disappear without medical attention in 36-48 hours after exposure. *See Section IV*

SECTION VII – DISPOSAL PROCEDURES

Sweep or shovel spilled material. If dust is generated, sweep or vacuum in a manner so as not to create additional contamination of area or air. Dispose of in a sanitary landfill in accordance with federal, state, and local regulations.

SECTION VIII – SPECIAL PROTECTION

Safety glasses with side shields are recommended, as are chemical resistant gloves, such as Nomex. No contact lenses. Use with appropriate local exhaust ventilation.

SECTION IX – OTHER PRECAUTIONS & COMMENTS

Store in cool, dry area. Keep away from heat.

Disclaimer

The information contained herein is accurate and reliable as of the date issued to the best of the manufacturer’s knowledge. ARGCO doesn’t warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising from the use thereof. It is the user’s responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

END OF MATERIAL SAFETY DATA SHEET