

data sheet


ARGCO

ALLIED RUBBER & GASKET COMPANY



2000° CERAMIC FIBER FIBER ROPE

- Non-asbestos
- Excellent high temperature seals & gaskets
- Excellent thermal shock & corrosion resistance
- 2300° F temperature rating
- Tapes and other textiles available



Multi-Ply Twisted Ceramic Fiber Rope (Made from Wicking)

These ropes are produced by twisting multiple plies of ceramic fiber wicking together.

Standard 3-ply twisted rope is relatively soft and low in density and is the most economical choice.

Applications:

- Furnace door insulation and seal
- Coke oven door jam seal
- Maintenance in aluminum plants
- Foundries, refineries and power plants
- Expansion joint packing
- Gasket for vacuum degassing of steel
- During pouring
- High temperature gasketing and packing
- Tadpole gasket bulb cord
- Expansion joint packing in boilers and furnaces
- Woodburning stove door seal
- Glass furnace truckstone seal

CHEMICAL CONTENTS

Alumina: 57%
Silica: 53%

PRODUCT PROPERTIES

Color: white
Normal Section Diameters: 1/4", 3/8", 1/2", 5/8", 3/4", 1", 1-1/4", 1-1/2", 2"
Density: 20-33
Tensile Strength: 75-100
Melting Point: 3200°
Continuous use up to °F: 2300°

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015
OR LOG ONTO WWW.ARGCO.COM**