

1000° FIBERGLASS ROPE

High Density and Low Density



Knitted 100% fiberglass rope offers the advantages of economy with more consistency and workability without sacrificing any of the physical, chemical or high temperature characteristics.

1000° F - available high density or low density.

- **High Density** is more firm, dense material that resembles twisted rope.
- **Low Density** is soft and easily compressible for gasketing, caulking for oven and furnace doors and expansion joints.



Made in USA

- Continuous protection to 1000° F (538° C)
- Non-asbestos
- Lightweight
- Strong & safe
- Abrasion resistant
- Low irritation factor
- Maximum flexibility
- Chemical resistant
- Specified for use by military
- Aluminized and wire inserted available



DIAMETER	HIGH DENSITY ITEM #	LOW DENSITY ITEM #	FT/LB.	FT/CASE
1/8"	1590200	-	150	3750
1/4"	1590201	1590211	45.5	1138
3/8"	1590202	1590212	25.0	625
1/2"	1590203	1590213	15.0	375
5/8"	1590204	1590214	10.0	250
3/4"	1590205	1590215	7.6	205
7/8"	-	1590216	5.5	138
1"	1590207	1590217	4.5	113
1-1/4"	1590208	-	3.0	75
1-1/2"	1590209	1590219	2.0	50

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	