

data sheet

ARGCO

ALLIED RUBBER & GASKET COMPANY



1000° FIBERGLASS TADPOLE TAPE

For boiler door and oven door seals

Typical Tadpole construction - a high-temp wrap over a core of soft fiberglass rope. The lip of the wrapping cloth extends to one side forming a flange. Secure the tape to the door frame with fasteners. The round portion of the tape is a cushion upon which the hatch is closed and forms a seal.

Min Temp: -40° F / -11° C
Max Temp: 1000° F / 538° C
Color / Finish: Off-White

The core (or head) consists of a bulb, which is the sealing area; the tail is used for fastening. Used where limited bolting force is available and where gasket must conform to uneven surfaces.



- Maximum flexibility
- Chemical resistant
- Specified for use by military (Government spec. HH-P-0031)
- Aluminized and wire inserted available
- Continuous protection to 1000° F (538° C)
- Non-asbestos
- Lightweight
- Strong & safe
- Abrasion resistant
- Low irritation factor

RUBBERIZED	PLAIN	SIZE
1530000	1531000	1" x 3/8" x 1/8" (100')
1530005	1531005	1" x 1/2" x 1/8" (100')
1530015	1531015	1/2" x 1/2" x 1/8" (100')
1530017	1531017	1-3/4" x 3/8" x 1/8" (100')
1530018	1531018	1-3/4" x 1/2" x 1/8" (100')
1530020	1531020	2" x 1/2" x 1/8" (100')
1530025	1531025	2" x 5/8" x 1/8" (100')
1530040	1531040	2-1/2" x 3/4" x 1/8" (100')

Call for quotes on square dry packing, vermiculite coated, and 2300°F temp. ropes.

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015
OR LOG ONTO WWW.ARGCO.COM**