

MALLEABLE IRON THREADED FITTINGS REDUCING 90° ELBOW

ASTM A 197- Standard Spec for Cupola Malleable Iron

ASTM A 153- Standard Spec for Zinc Coating (Hot Dip) on Iron and Steel

ANSI B 16.3- Malleable Iron Threaded Fittings Classes 150


ANSI/ASME B1.20.1- Pipe Threads, General Purpose (inch) NPT

ALL MALLEABLE THREADED FITTINGS MANUFACTURED FOR AND BY
UNIQUE FITTINGS & FLANGES® CONFORM TO, COMPLY WITH, AND ARE
MANUFACTURED TO THE FOLLOWING STANDARDS:

Dimensions: ANSI B16.3 CLASS 150 Coating: Black- none; Galvanized- Hot dip per ASTM A153

Material: Malleable Iron per ASTM A197 Threads: Pipe Threads, General Purpose ASME B1.20.1

DESCRIPTION
MALLEABLE 90 REDUCING BEND



NOM SIZE	ITEM CODE		DIMENSION		ITEM WEIGHT
	BLACK	GALV	A	B	
1/2" X 3/8"	1M90R0403	1M90R0403G	1.00	1.06	0.22
3/4" X 1/2"	1M90R0504	1M90R0504G	1.19	1.25	0.38
1" X 1/2"	1M90R0604	1M90R0604G	1.25	1.38	0.46
1" X 3/4"	1M90R0605	1M90R0605G	1.38	1.44	0.56
1 1/4" X 1/2"	1M90R0704	1M90R0704G	1.38	1.56	0.61
1 1/4" X 3/4"	1M90R0705	1M90R0705G	1.44	1.63	0.71
1 1/2" X 1/2"	1M90R0804	1M90R0804G	1.41	1.66	1.15
1 1/2" X 3/4"	1M90R0805	1M90R0805G	1.50	1.75	1.08
1 1/2" X 1"	1M90R0806	1M90R0806G	1.63	1.81	1.02
1 1/2" X 1 1/4"	1M90R0807	1M90R0807G	1.81	1.88	1.17
2" X 1/2"	1M90R0904	1M90R0904G	1.49	1.88	1.30
2" X 3/4"	1M90R0905	1M90R0905G	1.63	2.00	1.30
2" X 1"	1M90R0906	1M90R0906G	1.75	2.00	1.35
2" X 1 1/4"	1M90R0907	1M90R0907G	1.88	2.13	1.53
2" X 1 1/2"	1M90R0908	1M90R0908G	2.00	2.13	1.75

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 800-854-1015
OR LOG ONTO ARGCO.COM**