

MALLEABLE IRON THREADED FITTINGS REDUCING COUPLINGS

ASTM A 197- Standard Spec for Cupola Malleable Iron

ASTM A 153- Standard Spec for Zinc Coating (Hot Dip) on Iron and Steel

ANSI B 16.3- Malleable Iron Threaded Fittings Classes 150


ANSI/ASME B1.20.1- Pipe Threads, General Purpose (inch) NPT

ALL MALLEABLE THREADED FITTINGS MANUFACTURED FOR AND BY
UNIQUE FITTINGS & FLANGES® CONFORM TO, COMPLY WITH, AND ARE
MANUFACTURED TO THE FOLLOWING STANDARDS:

Dimensions: ANSI B16.3 CLASS 150 Coating: Black- none; Galvanized- Hot dip perASTM
A153

Material: Malleable Iron perASTM A197 Threads: Pipe Threads, General PurposeASME
B1.20.1

DESCRIPTION
MALLEABLE REDUCING
COUPLING



| NOM SIZE | ITEM CODE | | DIM. A | ITEM WEIGHT |
|-----------------|-----------|-----------|-----------|----------------|
| | BLACK | GALV | | |
| 1/2" X 3/8" | 1MCR0403 | 1MCR0403G | 1.25 | 0.17 |
| 3/4" X 1/2" | 1MCR0504 | 1MCR0504G | 1.44 | 0.27 |
| 1" X 1/2" | 1MCR0604 | 1MCR0604G | 1.69 | 0.39 |
| 1" X 3/4" | 1MCR0605 | 1MCR0605G | 1.69 | 0.43 |
| 1 1/4" X 1/2" | 1MCR0704 | 1MCR0704G | 2.06 | 0.61 |
| 1 1/4" X 3/4" | 1MCR0705 | 1MCR0705G | 2.06 | 0.64 |
| 1 1/4" X 1" | 1MCR0706 | 1MCR0706G | 2.06 | 0.68 |
| 1 1/2" X 1/2" | 1MCR0804 | 1MCR0804G | 2.31 | 0.78 |
| 1 1/2" X 3/4" | 1MCR0805 | 1MCR0805G | 2.31 | 0.88 |
| 1 1/2" X 1" | 1MCR0806 | 1MCR0806G | 2.31 | 0.88 |
| 1 1/2" X 1 1/4" | 1MCR0807 | 1MCR0807G | 2.31 | 0.90 |
| 2" X 1/2" | 1MCR0904 | 1MCR0904G | 2.81 | 1.15 |
| 2" X 3/4" | 1MCR0905 | 1MCR0905G | 2.81 | 1.34 |
| 2" X 1" | 1MCR0906 | 1MCR0906G | 2.81 | 1.40 |
| 2" X 1 1/4" | 1MCR0907 | 1MCR0907G | 2.81 | 1.53 |
| 2" X 1 1/2" | 1MCR0908 | 1MCR0908G | 2.81 | 1.55 |
| 2 1/2" X 1 1/4" | 1MCR1007 | 1MCR1007G | 3.25 | 2.09 |
| 2 1/2" X 1 1/2" | 1MCR1008 | 1MCR1008G | 3.25 | 2.09 |
| 2 1/2" X 2" | 1MCR1009 | 1MCR1009G | 3.25 | 2.51 |
| 3" X 1 1/4" | 1MCR1107 | 1MCR1107G | 3.69 | 2.99 |
| 3" X 1 1/2" | 1MCR1108 | 1MCR1108G | 3.69 | 3.30 |
| 3" X 2" | 1MCR1109 | 1MCR1109G | 3.69 | 3.25 |
| 4" X 1 1/2" | 1MCR1208 | 1MCR1208G | 4.38 | 4.90 |
| 4 X 2 | 1MCR1209 | 1MCR1209G | 4.38 | 5.10 |
| 4 X 3 | 1MCR1210 | 1MCR1210G | 4.38 | 6.55 |

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 800-854-1015
OR LOG ONTO ARGCO.COM**