

# data sheet

## **ARGCO**



## **HIGH DENSITY PTFE TAPE (0.8 density)**

### **APPLICATION**

For plumbers and pipe fitters.

Twice the density of standard white PTFE tape, making it easier to handle.

0.8 density tape is makes it unnecessary to wrap so many revolutions around the pipe.

Ensures leak free joints.

Exceeds MIL Spec T-27730A.

### **COMPOSITION**

Min. 99% virgin PTFE, Max. 1% Pigment

### **GENERAL APPEARANCE**

The tape appears pale pink in color. It shall be free of visible voids, cracks, folds, contamination and have consistent physical properties.

### **PACKAGING**

The 0.8 density expanded PTFE Thread Seal Tapes are wound in 1 inch 1D plastic spools unless otherwise specified.

Bulk packaging is sufficient to prevent damage during shipment.

**USEFUL TEMPERATURE RANGE:** -450°F to +500°F

**REACTIVITY:** Chemically inert to virtually all environments

**FLAMMABILITY:** Non-Flammable

**STORAGE:** Unlimited shelf-life (Less than 70° recommended)

Capable of sealing all liquids and gases.

Oxygen is the only exception.

ARGCO offers special green color coded tape for oxygen (item # 6010150)

### **ARGCO PART NUMBERS:**

6010162WH: 1/2" x 520"

6010167WH: 3/4" x 520"

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015  
OR LOG ONTO WWW.ARGCO.COM**