

PERSONALIZED HYDRAULIC SYSTEM SIGNS



HYDRAULIC - SYSTEM	
This building is protected by a Hydraulically Designed Automatic Sprinkler System	
Location	<input type="text"/>
No. of Sprinklers	<input type="text"/>
Basis of Design	
1. DENSITY	<input type="text"/> GPM/SQ. FT.
2. DESIGNED AREA OF DISCHARGE	<input type="text"/> SQ. FT.
System Demand	
1. GPM DISCHARGE	<input type="text"/> GPM
2. RESIDUAL PRESSURE AT THE BASE OF THE RISER	<input type="text"/> PSI
<input type="text"/>	

5" x 7" White Aluminum Signs with Red Lettering. .040 thickness material with holes in 4 corners. Personalized with your company logo and contact information. Seven styles available.

Once you place your order, email your company logo and any additional information to our art department, you will receive a proof and once you approve, your signs will be printed.

Available in aluminum vinyl, or silver embossible foil.

A. (STANDARD)

HYDRAULIC - SYSTEM	
This building is protected by a Hydraulically Designed Automatic Sprinkler System	
Date Installed	<input type="text"/> Month <input type="text"/> Day <input type="text"/> Year
Location	<input type="text"/>
No. of Sprinklers	<input type="text"/>
Basis of Design	
1. Density	<input type="text"/> GPM/SQ. FT.
2. Designed area of discharge	<input type="text"/> SQ. FT.
System Demand	
1. Water flow rate	<input type="text"/> GPM
2. Residual pressure at the base of the riser	<input type="text"/> PSI
Installed by:	
<input type="text"/>	

B.

HYDRAULIC SYSTEM	
This building is protected by a Hydraulically Designed Automatic Sprinkler System	
DATE	<input type="text"/> MO/YR
Location	<input type="text"/>
Basis of Design	
1. DENSITY	<input type="text"/> GPM/SQ. FT.
2. DESIGNED AREA OF DISCHARGE	<input type="text"/>
System Demand	
1. GPM DISCHARGE	<input type="text"/> GPM
2. RESIDUAL PRESSURE AT THE BASE OF THE RISER	<input type="text"/> PSI
3. HOSE STREAM ALLOWANCE	<input type="text"/> GPM
OCCUPANCY CLASSIFICATION	<input type="text"/>
COMMODITY CLASSIFICATION	<input type="text"/>
MAXIMUM STORAGE HEIGHT	<input type="text"/>
<input type="text"/>	

C.

HYDRAULIC SYSTEM	
This building is protected by a Hydraulically Designed Automatic Sprinkler System	
Location	<input type="text"/>
No. of Sprinklers	<input type="text"/>
Basis of Design	
1. DENSITY	<input type="text"/> GPM/SQ. FT.
2. DESIGNED AREA OF DISCHARGE	<input type="text"/> SQ. FT.
System Demand	
1. GPM DISCHARGE	<input type="text"/> GPM
2. RESIDUAL PRESSURE AT THE BASE OF THE RISER	<input type="text"/> PSI
3. HOSE STREAM ALLOWANCE	<input type="text"/> GPM
4. OCCUPANCY CLASSIFICATION	<input type="text"/>
5. COMMODITY CLASSIFICATION	<input type="text"/>
6. MAXIMUM STORAGE HEIGHT	<input type="text"/>
<input type="text"/>	

D.

HYDRAULIC SYSTEM	
This building is protected by a Hydraulically Designed Automatic Sprinkler System	
Date Installed	<input type="text"/> Month <input type="text"/> Day <input type="text"/> Year
Location	<input type="text"/>
Design Basis	
1. Density	<input type="text"/> GPM/SQ. FT.
2. Area	<input type="text"/> SQ. FT.
3. No. of Sprinklers	<input type="text"/>
4. Classification	<input type="text"/>
5. Max storage height	<input type="text"/> FT.
Demand	
1. Water flow rate	<input type="text"/> GPM
2. Residual pressure at the base of the riser	<input type="text"/> PSI
3. Hose Stream allowance	<input type="text"/> GPM
<input type="text"/>	

E.

HYDRAULIC SYSTEM	
This system as shown on print no. <input type="text"/>	
dated <input type="text"/> for <input type="text"/>	
at <input type="text"/> contract no. <input type="text"/>	
Is designed to discharge at a rate of <input type="text"/> gpm(L/min)	
of floor area over a maximum area of <input type="text"/> ft ² (m ²)	
when supplied with water at a rate of <input type="text"/> gpm(L/min)	
at the base of the riser.	
Hose stream allowance of <input type="text"/> gpm(L/min)	
is included above.	
Occupancy classification	<input type="text"/>
Commodity classification	<input type="text"/>
Maximum storage height	<input type="text"/>
<input type="text"/>	

F.

Hydraulically Calculated System	
This system as shown on <input type="text"/>	
company print no <input type="text"/> dated <input type="text"/>	
for <input type="text"/>	
at <input type="text"/> cont. no <input type="text"/>	
is designed to discharge at a rate of <input type="text"/> gpm	
(L/min per sq ft (m ²) of floor area over a maximum area of	
<input type="text"/> sq ft (m ²) when supplied	
with water at the rate of <input type="text"/> gpm (L/min)	
at <input type="text"/> psi (bars) at the base of the riser.	
Hose stream allowance of <input type="text"/> gpm (L/min)	
Is Included in the above.	
Occupancy classification	<input type="text"/>
Commodity classification	<input type="text"/>
Maximum storage height	<input type="text"/>
Installed by: <input type="text"/>	

G.